



The World Leader in Performance Silicone Hoses 2011

ProFuel™ - Fuel Resistant Elbows



Bore mm	Bore "	Wall Size	Leg Length	UK RRP £ (Exc. VAT)	UK RRP £ (Exc. VAT)	UK RRP £ (Exc. VAT)
				PE90	PE45	PE135
6.5	1/4"	4.2mm	63mm	10.86	10.86	10.86
8	5/16"	4.2mm	63mm	11.88	11.88	11.99
9.5	3/8"	4.2mm	63mm	12.82	12.82	13.07
11	7/16"	4.2mm	63mm	13.84	13.84	14.04
13	1/2"	4.2mm	102mm	15.35	15.35	15.58
16	5/8"	4.2mm	102mm	16.14	16.14	16.75
18		4.2mm	102mm	16.81	16.81	-
19	3/4"	4.2mm	102mm	17.16	17.16	17.88
20	25/32"	4.2mm	102mm	17.27	-	-
22	7/8"	4.2mm	102mm	18.01	18.01	19.42
25	1"	4.2mm	102mm	19.83	19.83	20.92
28	1 1/8"	4.2mm	102mm	21.05	21.05	21.85
30	1 3/16"	4.2mm	102mm	22.25	22.25	23.94
32	1 1/4"	4.2mm	102mm	22.81	22.81	24.24
35	1 3/8"	4.2mm	102mm	25.08	25.08	26.52
38	1 1/2"	4.2mm	102mm	26.16	26.16	28.34
41	1 5/8"	4.2mm	102mm	27.80	27.80	30.02
45	1 3/4"	4.2mm	102mm	29.15	29.15	32.96
48	1 7/8"	4.2mm	102mm	31.27	31.27	34.38
51	2"	5.2mm	102mm	34.84	34.84	37.98
54	2 1/8"	5.2mm	102mm	38.29	38.29	39.35
57	2 1/4"	5.2mm	102mm	41.05	41.05	41.91
60	2 3/8"	5.2mm	125mm	43.75	43.75	48.15
63	2 1/2"	5.2mm	125mm	46.11	46.11	51.38
65	2 9/16"	5.2mm	125mm	47.33	47.33	54.29
68	2 11/16"	5.2mm	125mm	49.65	49.65	57.68
70	2 3/4"	5.2mm	125mm	50.88	50.88	59.77
76	3"	5.2mm	125mm	55.07	55.07	66.41
80	3 1/8"	5.2mm	125mm	57.98	57.98	71.21
83	3 1/4"	5.2mm	125mm	60.36	60.36	74.95
89	3 1/2"	6.0mm	125mm	63.46	63.46	89.50
102	4"	6.0mm	152mm	73.88	73.88	109.00

Order example... PE90-63

PE90 : Fuel Resistant - ProFuel™
The World's first Performance Silicone hose for permanent fuel use. Suitable for transport of Petroleum & Diesel Fuels –can be used for fuel lines, delivery, filler and breathers. 2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
 Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey
(+35%) : Samco Blaze / Urban Camo
 Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)



The World Leader in Performance Silicone Hoses 2011



120° & 60° Standard Elbows

Bore mm	Bore "	Wall Size	Leg Length	UK RRP £ (Exc. VAT)	
				60° Standard	120° Standard
				PE60	PE120
6.5	1/4"	4.0mm	63mm	10.86	10.86
8	5/16"	4.0mm	63mm	11.88	11.99
9.5	3/8"	4.0mm	63mm	12.82	13.07
11	7/16"	4.0mm	63mm	13.84	14.04
13	1/2"	4.0mm	102mm	15.35	15.58
16	5/8"	4.0mm	102mm	16.14	16.75
18	45/64"	4.0mm	102mm	16.81	-
19	3/4"	4.0mm	102mm	17.16	17.88
20	25/32"	4.0mm	102mm	-	-
22	7/8"	4.0mm	102mm	18.01	19.42
25	1"	4.0mm	102mm	19.83	20.92
28	1 1/8"	4.0mm	102mm	21.05	21.85
30	1 3/16"	4.0mm	102mm	22.25	23.94
32	1 1/4"	4.0mm	102mm	22.81	24.24
35	1 3/8"	4.0mm	102mm	25.08	26.52
38	1 1/2"	4.0mm	102mm	26.16	28.34
41	1 5/8"	4.0mm	102mm	27.80	30.02
45	1 3/4"	4.0mm	102mm	29.15	32.96
48	1 7/8"	4.0mm	102mm	31.27	34.38
51	2"	5.0mm	102mm	34.84	37.98
54	2 1/8"	5.0mm	102mm	38.29	39.35
57	2 1/4"	5.0mm	102mm	41.05	41.91
60	2 3/8"	5.0mm	125mm	43.75	48.15
63	2 1/2"	5.0mm	125mm	46.11	51.38
65	2 9/16"	5.0mm	125mm	47.33	54.29
68	2 11/16"	5.0mm	125mm	49.65	57.68
70	2 3/4"	5.0mm	125mm	50.88	59.77
76	3"	5.0mm	125mm	55.07	66.41
80	3 1/8"	5.0mm	125mm	57.98	71.21
83	3 1/4"	5.0mm	125mm	60.36	74.95
89	3 1/2"	6.3mm	125mm	63.46	89.50
102	4"	6.3mm	152mm	73.88	109.00

E60: Standard Polyester Silicone 45° Elbow
E120: Standard Polyester Silicone 135° Elbow

E60-51
E120-51

Standard Colour Options : Blue / Red / Bright Green / Yellow
 Purple / Black / B.R. Green / Orange
Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey
 (+35%) : Samco Blaze / Urban Camo
 Solar Orange Camo / Lightning Blue / Ninja Green
Hose Max Temperature : 180°C (356°F)



ProFuel™ - Fuel Resistant Elbow Reducers

Bore > Bore mm	Bore > Bore "	Wall Size	Length	UK RRP £ (Exc. VAT) PRE90	UK RRP £ (Exc. VAT) PRE45
12-9	1/2" > 3/8"	4.0mm	102mm	15.35	-
16-13	5/8" > 1/2"	4.0mm	102mm	16.13	-
19-13	3/4" > 1/2"	4.0mm	102mm	17.16	-
19-16	3/4" > 5/8"	4.0mm	102mm	17.16	-
22-16	7/8" > 5/8"	4.0mm	102mm	18.01	-
22-19	7/8" > 3/4"	4.0mm	102mm	18.01	-
25-19	1" > 3/4"	4.0mm	102mm	19.84	-
32-19	1 1/4" > 3/4"	4.0mm	102mm	19.84	-
32-25	1 1/4" > 1"	4.0mm	102mm	22.81	-
32-28	1 1/4" > 1 1/8"	4.0mm	102mm	22.81	-
35-22	1 3/8" > 7/8"	4.0mm	102mm	25.08	25.08
35-25	1 3/8" > 1"	4.0mm	102mm	25.08	-
35-30	1 3/8" > 1 3/16"	4.0mm	102mm	25.08	-
35-32	1 3/8" > 1 1/4"	4.0mm	102mm	25.08	-
38-16	1 1/2" > 5/8"	4.0mm	102mm	-	26.15
38-25	1 1/2" > 1"	4.0mm	102mm	26.15	-
38-32	1 1/2" > 1 1/4"	4.0mm	102mm	26.15	-
38-35	1 1/2" > 1 3/8"	4.0mm	102mm	26.15	-
41-35	1 5/8" > 1 3/8"	4.0mm	102mm	-	27.79
42-32	1 5/8" > 1 1/2"	4.0mm	102mm	27.79	-
45-32	1 3/4" > 1 1/4"	4.0mm	102mm	29.15	-
45-35	1 3/4" > 1 3/8"	4.0mm	102mm	29.15	-
45-38	1 3/4" > 1 1/2"	4.0mm	102mm	29.15	29.15
48-30	1 7/8" > 1 3/16"	4.0mm	102mm	31.27	-
48-38	1 7/8" > 1 1/2"	4.0mm	102mm	31.27	-
51-38	2 1/4" > 1 1/2"	5.0mm	102mm	34.84	34.84
51-45	2 1/4" > 1 3/4"	5.0mm	102mm	34.84	34.84
54-48	2 1/8" > 1 7/8"	5.0mm	102mm	38.29	-
55-42	2 1/8" > 1 5/8"	5.0mm	102mm	-	38.29
57-51	2 1/4" > 2"	5.0mm	102mm	41.05	41.05
60-51	2 3/8" > 2"	5.0mm	125mm	43.75	43.75
60-55	2 3/8" > 2 1/8"	5.0mm	125mm	-	43.75
60-57	2 3/8" > 2 1/4"	5.0mm	125mm	-	0.00
63-51	2 1/2" > 2"	5.0mm	125mm	46.11	43.75
63-57	2 1/2" > 2 1/4"	5.0mm	125mm	46.11	-
65-50	2 9/16" > 2"	5.0mm	125mm	47.34	-
65-60	2 9/16" > 2 3/8"	5.0mm	125mm	47.34	47.34
70-51	2 3/4" > 2"	5.0mm	125mm	50.87	50.87
70-60	2 3/4" > 2 3/8"	5.0mm	125mm	50.87	50.87
70-63	2 3/4" > 2 1/2"	5.0mm	125mm	50.87	-
76-51	3" > 2"	5.0mm	125mm	55.07	55.07
76-60	3" > 2 3/8"	5.0mm	125mm	55.07	-
76-63	3" > 2 1/2"	5.0mm	125mm	55.07	55.07
76-70	3" > 2 3/4"	5.0mm	125mm	55.07	-
80-60	2 1/8" > 2 1/2"	5.0mm	125mm	57.98	-
80-70	3 1/8" > 2 3/4"	5.0mm	125mm	57.98	57.98
89-65	3 1/2" > 2 9/16"	6.0mm	125mm	63.46	-
89-76	3 1/2" > 3"	6.0mm	125mm	63.46	-
100-90	4" > 3 1/2"	6.0mm	152mm	73.87	73.87
102-76	4" > 3"	6.0mm	152mm	73.87	-

Order example...

PRE90 16-13

PRE90 :

Fuel Resistant - ProFuel™

The World's first Performance Silicone hose for permanent fuel use.

Suitable for transport of Petroleum & Diesel Fuels –can be used for fuel lines, delivery, filler and breathers.

2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey

(+35%) : Samco Blaze / Urban Camo

Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)



ProFuel™ Straight Hose x 1m (3'3") long

UK RRP £ (Exc. VAT)
ProFuel
PSHL

Bore mm	Bore "	Wall Size	UK RRP £ (Exc. VAT) ProFuel PSHL
6.5	1/4"	3.9mm	33.10
8	5/16"	3.9mm	35.77
9.5	3/8"	3.9mm	44.14
11	7/16"	3.9mm	45.68
13	1/2"	3.9mm	50.00
16	5/8"	3.9mm	54.59
18	45/64"	3.9mm	57.84
19	3/4"	3.9mm	59.68
20	25/32"	3.9mm	61.12
22	7/8"	3.9mm	62.57
25	1"	3.9mm	66.96
28	1 1/8"	3.9mm	71.41
30	1 3/16"	3.9mm	76.60
32	1 1/4"	3.9mm	78.45
35	1 3/8"	3.9mm	84.26
38	1 1/2"	3.9mm	87.76
41	1 5/8"	3.9mm	92.19
45	1 3/4"	3.9mm	99.54
48	1 7/8"	3.9mm	105.06
51	2"	5.2mm	108.16
54	2 1/8"	5.2mm	115.04
57	2 1/4"	5.2mm	120.43
60	2 3/8"	5.2mm	128.67
63	2 1/2"	5.2mm	134.18
65	2 9/16"	5.2mm	138.36
68	2 11/16"	5.2mm	143.87
70	2 3/4"	5.2mm	148.30
76	3"	5.2mm	159.32
80	3 1/8"	5.2mm	167.70
83	3 1/4"	5.2mm	173.21
89	3 1/2"	6.5mm	199.40
102	4"	6.5mm	225.49
110	4 1/3"	6.5mm	245.41
114	4 1/2"	6.5mm	262.13
127	5"	6.5mm	315.43
152	6"	6.5mm	348.55
200	8"	6.5mm	446.16

Order example...

PSHL6.6

Fuel Resistant - ProFuel™ SHL :

The World's first Performance Silicone hose for permanent fuel use. Suitable for transport of Petroleum & Diesel Fuels –can be used for fuel lines, delivery, filler and breathers. Also Available on most race parts. 2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow

Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey

(+35%) : Samco Blaze / Urban Camo

Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)



The World Leader in Performance Silicone Hoses 2011



ProFuel™ Fuel Resistant Xtraflex Hose x 1m (3'3")

<i>Bore mm</i>	<i>Bore "</i>	<i>Wall Size</i>	UK RRP £(Exc. VAT) PXFL
6.5	1/4"	3.5mm	51.31
8	5/16"	3.5mm	55.44
9.5	3/8"	3.5mm	68.42
11	7/16"	3.5mm	70.82
13	1/2"	3.5mm	78.99
16	5/8"	3.5mm	86.26
18	45/64"	3.5mm	89.94
19	3/4"	3.5mm	94.29
20	25/32"	3.5mm	96.97
22	7/8"	3.5mm	103.79
25	1"	3.5mm	107.13
28	1 1/8"	3.5mm	113.37
30	1 3/16"	3.5mm	113.75
32	1 1/4"	3.5mm	122.19
35	1 3/8"	3.5mm	124.62
38	1 1/2"	3.5mm	130.91
41	1 5/8"	3.5mm	139.36
45	1 3/4"	3.5mm	147.09
48	1 7/8"	3.5mm	151.43
51	2"	3.5mm	161.05

Order example...

PXFL6.5

PXFL : Fuel Resistant - ProFuel™ XFL :

The World's first Performance Silicone hose for permanent fuel use.
Suitable for transport of Petroleum & Diesel Fuels –can be used
for fuel lines, delivery, filler and breathers.
2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
 Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey
(+35%) : Samco Blaze / Urban Camo
 Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)



ProFuel™ Resistant Straight Reducers

UK RRP £
(Exc. VAT)

Bore > Bore mm	Bore > Bore "	Wall Size	Length	PSR
12-8	1/2" > 5/16"	4.2mm	102mm	12.08
12.7-9.5	1/2" > 3/8"	4.2mm	102mm	12.16
16-13	5/8" > 1/2"	4.2mm	102mm	13.55
19-13	3/4" > 1/2"	4.2mm	102mm	13.85
19-16	3/4" > 5/8"	4.2mm	102mm	13.85
22-16	7/8" > 5/8"	4.2mm	102mm	14.38
22-19	7/8" > 3/4"	4.2mm	102mm	14.38
25-16	1" > 5/8"	4.2mm	102mm	15.46
25-19	1" > 3/4"	4.2mm	102mm	15.46
25-22	1" > 7/8"	4.2mm	102mm	15.46
28-22	1 1/8" > 7/8"	4.2mm	102mm	15.42
28-25	1 1/8" > 1"	4.2mm	102mm	15.42
32-19	1 1/4" > 3/4"	4.2mm	102mm	17.36
32-25	1 1/4" > 1"	4.2mm	102mm	17.36
32-28	1 1/4" > 1 1/8"	4.2mm	102mm	17.58
35-25	1 3/8" > 1"	4.2mm	102mm	18.60
35-28	1 3/8" > 1 1/8"	4.2mm	102mm	18.60
35-32	1 3/8" > 1 1/4"	4.2mm	102mm	18.60
38-22	1 1/2" > 7/8"	4.2mm	102mm	19.93
38-25	1 1/2" > 1"	4.2mm	102mm	19.93
38-28	1 1/2" > 1 1/8"	4.2mm	102mm	19.93
38-32	1 1/2" > 1 1/4"	4.2mm	102mm	19.93
38-35	1 1/2" > 1 3/8"	4.2mm	102mm	19.93
40-35	1 5/8" > 1 3/8"	4.2mm	102mm	20.60
41-38	1 5/8" > 1 1/2"	4.2mm	102mm	20.93
45-32	1 3/4" > 1 1/4"	4.2mm	102mm	21.69
45-38	1 3/4" > 1 1/2"	4.2mm	102mm	21.69
51-38	2" > 1 1/2"	5.2mm	102mm	24.15
51-45	2" > 1 3/4"	5.2mm	102mm	24.15
54-51	2 1/8" > 2"	5.2mm	102mm	25.17
57-51	2 1/4" > 2"	5.2mm	102mm	26.17
60-50	2 3/8" > 2"	5.2mm	125mm	27.01
63-51	2 1/2" > 2"	5.2mm	125mm	27.44
63-57	2 1/2" > 2 1/4"	5.2mm	125mm	27.44
63-60	2 1/2" > 2 3/8"	5.2mm	125mm	27.44
65-60	2 9/16" > 2 3/8"	5.2mm	125mm	28.07
70-50	2 3/4" > 2"	5.2mm	125mm	29.72
70-57	2 3/4" > 2 1/4"	5.2mm	125mm	29.72
70-60	2 3/4" > 2 3/8"	5.2mm	125mm	29.72
70-63	2 3/4" > 2 1/2"	5.2mm	125mm	29.72
76-51	3" > 2"	5.2mm	125mm	31.62
76-57	3" > 2 1/4"	5.2mm	125mm	33.01
76-60	3" > 2 3/8"	5.2mm	125mm	33.01
76-63	3" > 2 1/2"	5.2mm	125mm	33.01
76-67	3" > 2 5/8"	5.2mm	125mm	33.01
76-70	3" > 2 3/4"	5.2mm	125mm	33.01
80-51	3 1/8" > 2"	5.2mm	125mm	34.25
80-65	3 1/8" > 2 9/16"	5.2mm	125mm	34.25
80-70	3 1/8" > 2 3/4"	5.2mm	125mm	34.25
80-76	3 1/8" > 3"	5.2mm	125mm	34.25
83-76	3 1/4" > 3"	5.2mm	125mm	35.21
89-63	3 1/2" > 2 1/2"	6.0mm	125mm	39.21
89-76	3 1/2" > 3"	6.0mm	125mm	39.21
90-80	3 1/2" > 3 1/8"	6.0mm	125mm	39.54
102-76	4" > 3"	6.0mm	152mm	49.94
102-83	4" > 3 1/4"	6.0mm	152mm	49.94
102-89	4" > 3 1/2"	6.0mm	152mm	49.94
127-100	5" > 4"	6.0mm	152mm	61.63

Order example... **PSR90 16-13**

Fuel Resistant - ProFuel™

The World's first Performance Silicone hose for permanent fuel use.

Suitable for transport of Petroleum & Diesel Fuels –can be used for fuel lines, delivery, filler and breathers.

2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey

(+35%) : Samco Blaze / Urban Camo

Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)



ProFuel™ Resistant Coupling Hose

Bore mm	Bore "	Wall Size	Length	Part Code	UK RRP £ (Exc. VAT) PSCH
51	2"	5.2mm	76mm	PSCH51	9.26
54	2 1/8"	5.2mm	76mm	PSCH54	9.67
57	2 1/4"	5.2mm	76mm	PSCH57	10.30
60	2 3/8"	5.2mm	76mm	PSCH60	10.73
63	2 1/2"	5.2mm	76mm	PSCH63	11.05
65	2 9/16"	5.2mm	76mm	PSCH65	11.49
68	2 11/16"	5.2mm	76mm	PSCH68	11.81
70	2 3/4"	5.2mm	76mm	PSCH70	12.67
76	3"	5.2mm	76mm	PSCH76	13.30
80	3 1/8"	5.2mm	76mm	PSCH80	13.73
83	3 1/4"	5.2mm	76mm	PSCH83	15.75
89	3 1/2"	6.0mm	76mm	PSCH89	17.75
102	4"	6.0mm	76mm	PSCH102	19.28

Order example... **PSCH51**

Fuel Resistant - ProFuel™
The World's first Performance Silicone hose for permanent fuel use.
Suitable for transport of Petroleum & Diesel Fuels –can be used
for fuel lines, delivery, filler and breathers.
2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
 Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey
(+35%) : Samco Blaze / Urban Camo
 Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)

ProFuel™ Resistant Hump Hose



Bore mm	Bore "	Wall Size	Length	Part Code	UK RRP £ (Exc. VAT) PSHH
45	1 3/4"	5.2mm	76mm	PSHH45	19.17
50	2 "	5.2mm	76mm	PSHH50	19.09
60	2 3/8"	5.2mm	76mm	PSHH60	21.16
63	2 1/2"	5.2mm	76mm	PSHH63	21.73
70	2 3/4"	5.2mm	76mm	PSHH70	22.77
76	3"	5.2mm	76mm	PSHH76	23.91
80	3 1/8"	5.2mm	76mm	PSHH80	25.38
90	3 1/2"	6.0mm	76mm	PSHH90	29.72
100	4"	6.0mm	76mm	PSHH100	31.78

Order example... **PSHH45**

Fuel Resistant - ProFuel™
The World's first Performance Silicone hose for permanent fuel use.
Suitable for transport of Petroleum & Diesel Fuels –can be used
for fuel lines, delivery, filler and breathers.
2 Year Warranty. Supplied with ProFuel™ green lining.

Standard Colour Options : Blue / Red / Bright Green / Yellow
 Purple / Black / B.R. Green / Orange

Premium Colour Options (+15%) : White / Silver / Pink / Classic Black / Gunmetal Grey
(+35%) : Samco Blaze / Urban Camo
 Solar Orange Camo / Lightning Blue / Ninja Green

Hose Max Temperature : 180°C (356°F)